

## 48 端口 10/100BASE-TX RJ45 接口板 – LSB2FT48

### 1 单板标识

LSB2FT48 系列单板包括 LSB2FT48B0 和 LSB2FT48CA0。前面板右上角分别标有丝印: FT48B 和 FT48CA, 用来标识对应的单板。

### 2 单板简介

表1 单板属性

属性	规格
接口连接器类型	RJ45
接口数量	48
接口传输速率	10Mbps, 半双工/全双工 100Mbps, 半双工/全双工
可选用线缆及最大传输距离	5 类双绞线, 100m
单板适用的机型	S9502/S9505/S9508/S9508V/S9512
单板适用的主机软件版本	1272 及以上版本

### 3 注意事项

如主机软件版本不匹配, 请联系该设备的销售商或集成商获取相应的主机软件版本; 单板安装说明及主机软件版本的升级方法请参见《H3C S9500 系列路由交换机 安装手册》相关章节。

单板种类或规格可能随产品版本的变更而改变, 请从公司网站<http://www.h3c.com.cn>主页上的“文档中心”获取最新资料。

杭州华三通信技术有限公司

# 48-Port 10/100BASE-TX RJ45 Interface Card – LSB2FT48

## 1 Card Identifier

LSB2FT48 Series Cards include LSB2FT48B0 and LSB2FT48CA0. The silkscreens, FT48B and FT48CA, are printed at the upper right corner of each front panel respectively to identify the cards.

## 2 Specifications

**Table1** Card specifications

Item	Specification
Connector	RJ45
Port quantity	48
Transmission rate	10Mbps, Half duplex /Full duplex 100Mbps, Half duplex /Full duplex
Cable	Category 5 UTP
Maximum transmission distance	100m
Applied to	S9502/S9505/S9508/S9508V/S9512
Host software version	Version 1272 and above

## 3 Note

If the host software version does not match the one applicable to the card, contact the vendor or the integrator for the right version.

For the introduction of card installation and host software upgrade, see the related part in *H3C S9500 Series Routing Switches Installation Manual*.

As board types or specifications might change with product versions, you may need to obtain the latest documents from Technical Support & Document link on H3C website <http://www.h3c.com>.

Hangzhou H3C Technologies Co., Ltd